

"GIM-N" Series

GHIACCIO GRANULARE MODELLABILE
MOULDABLE GRANULAR ICE



Ice-Tek®

BY
MINERVA
OMEGA
GROUP

GIM 360N/452 - GIM 500N/452 - GIM 500NE SPLIT/452 - GIM 750N/452 GIM 750NE SPLIT/452 - GIM 1000N/452 - GIM 1000NE SPLIT/452 PRODUTTORI GHIACCIO MODELLABILE - MOULDBLE ICE MAKERS




- Costruzione in acciaio inox e materiali idonei al contatto con gli alimenti
- Gas R 452 A
- Condensazione (A) aria o (W) acqua*
- Versioni Compact e Split**
- Voltaggi speciali, su richiesta
- Comandi "ON-OFF" a bordo macchina
- Macchine rispondenti alle normative di igiene e di sicurezza in vigore
- **Condizioni di lavoro standard:**
 - temperatura acqua 15°C
 - temperatura ambiente 20°C
 - pressione acqua MIN 1 bar / MAX 5 bar




- Construction in stainless steel and specific materials approved for contact with food stuff
- Gas R 452 A
- (A) Air or W (Water) condensing*
- Compact and Split** versions
- Special voltages, on request
- "ON-OFF" controls on board the machine
- Machines comply with hygiene and safety regulations
- **Standard working conditions:**
 - incoming water temperature 15°C
 - environment air temperature 20°C
 - water pressure MIN 1 bar / MAX 5 bar

		GIM 360N/452	GIM 500N/452	GIM 500NE SPLIT/452 **	GIM 750N/452	GIM 750NE SPLIT/452 **	GIM 1000N/452	GIM 1000NE SPLIT/452 **
Gas		R 452 A	R 452 A	R 452 A	R 452 A	R 452 A	R 452 A	R 452 A
Produzione Productivity	kg/24h	360	500	500	750	750	1000	1000
Temperatura ghiaccio Ice temperature	°C	0	0	0	0	0	0	0
Potenza frigorifera richiesta Refrigerating capacity required	kW	-	-	1,73	-	3,3	-	6,8
Potenza elettrica Electrical Power	kW	1,09	1,4	0,4	2,4	0,40	4,4	0,80
Peso netto Net weight	kg	85	98	65	128	85	203	140
Tensione nominale Volt Rated	V/ph/Hz	230/1/50	230/1/50	230/1/50	400/3/50	230/1/50	400/3/50	230/1/50



GIM 360N/452 - GIM 500N/452
GIM 500NE SPLIT/452 - GIM 750N/452 - GIM 750NE SPLIT/452



GIM 1000N/452 - GIM 1000NE SPLIT/452

		GIM 360N/452	GIM 500N/452 GIM 500NE SPLIT/452	GIM 750N/452 GIM 750NE SPLIT/452	GIM 1000N/452 GIM 1000NE SPLIT/452
A	mm	638	740	877	877
B	mm	630	630	660	660
C	mm	545	545	640	640

Versione senza rivestimento da confermare - Naked version to be confirmed

* Da confermare - To be confirmed

** Valvola KVP esclusa (optional) - KVP valve not included (optional)

ACCESSORI - ACCESSORIES



Minerva Omega group s.r.l.
Via del Vetraino, 36 - 40138 Bologna - Italy
tel. +39 051 530.174 - fax +39 051 535.327
laminerva@laminerva.it
www.minervaomegagroup.com
UNI EN ISO 9001: 2015 - REG. N. 9656-A

